

DCP552 Digital Controller/ Programmer (Universal Input/Output Model)

Model Selection Guide

Instructions

- Select the desired Key Number. The arrow to the right marks the selections available.
 - Make one selection each from Table I through V, using the column below the proper arrow. A dot (•) denotes unrestricted availability. A letter denotes restricted availability.
 - A complete Model Number must have a selection for the Key Number and each table.
- Key Number** I II III IV V

KEY NUMBER	Selection	Availability
Description		
Two-Channel Digital Controller/Programmer	DCP552	↓

TABLE I

Output	Universal Output	F	•
--------	------------------	---	---

TABLE II

Input Selection	Two Inputs	2	•
-----------------	------------	---	---

TABLE III

Carbon	None	0	•
Potential	Oxygen Sensor Input for Carbon Potential (Note 1)	1	•

TABLE IV

Auxiliary	None	0	•
Output	1 Auxiliary Output	1	•
	2 Auxiliary Outputs and Communication (RS485 or RS232-C)	2	•

TABLE V

Extended	None	00	•
Warranty	Extended Warranty - 1 yr.	01	•
	Extended Warranty - 2 yr.	02	•

MEMORY CARDSOrder by separate Part Number

	Part Number
Memory Card - 64K	SKM064A-E0
Smart Loader Package Kit (SLP)	50035822-501

Note 1: Any Oxygen Sensor made by NGK Insulators, Ltd., Marathon Monitor Co., Cambridge Co., Corning Co., AACC (Advanced Atmosphere Control Corporation) Co., Barber Colman Co., and Furnace Control Co., can be used.